

PLANNING DIMENSIONS

All dimensions in millimetres

Full overlay		K0	Half overlay		K8	
Mounting plate height 2			Mounting plate height 2			
Door overlay	Cup distance					
	0	3	4	5	6	7
	20					0
	19				0	
	18			0	2	3
	17		0	2	3	4
	16	0	2	3	4	
	15		2	3	4	
	14	2	3	4		
	13	3	4			
12	4					
Mounting plate height						
Door overlay	Cup distance					
	8	3	4	5	6	7
	12					0
	11				0	
	10			0	2	3
	9		0	2	3	4
	8	0	2	3	4	
	7		2	3	4	
	6	2	3	4		
	5	3	4			
4	4					
Mounting plate height						

MINIMUM GAP

Door thickness	Cup distance				
	3	4	5	6	7
16	0.5	0.6	1.6	2.6	3.6
18	0.5	1.2	2.2	3.2	4.2
19	0.5	1.5	2.5	3.5	4.5
20	0.8	1.8	2.8	3.8	4.8
22	1.4	2.4	3.4	4.4	5.4
Minimum gap					

MINIMUM REVEAL

Door thickness	Cup distance				
	3	4	5	6	7
16	0.5	0.5	0.5	0.5	0.5
18	1.0	1.0	1.0	1.0	1.0
19	1.2	1.2	1.2	1.2	1.2
20	2.2	1.5	1.5	1.5	1.5
22	4.7	3.7	2.8	2.1	2.1
Minimum reveal (F)					

NOTES

The minimum gap is the clearance required between the front edge of the cabinet and the closed door so that the door can be opened without hindrance.


Important: Reveals were determined with a (door) edge radius of 1 mm.

Hinge dimensions and reveal calculation with factory setting.


We recommend a trial fitting.

DRILLING PATTERNS

For screw fitting



For press fitting



CUP DIMENSIONS

