

# Prime SLIM Soft Closing Drawer PRMSL86/PRMSL118/PRMSL167/PRMSL199

**GALVIN HARDWARE  
PRIME SL INSTALLATION INFO**

### Basic components

### Cutting dimensions of 16mm thick MDF

Back panel  
Bottom plate  
Wood backplane  
16mm: L=NL-24

	H
PRMSL86	86
PRMSL118	118
PRMSL167	167
PRMSL199	199

KB : Cabinet width  
LW : Internal cabinet width  
NL : Nominal length  
H : Back panel height

### Drawer installation to the cabinet.

“Click”

### Cabinet space requirements

PRMSL86    PRMSL118    PRMSL167    PRMSL199

### Front panel drilling dimensions

	E (min)	F (min)	G (min)	J (min)	K	L
PRMSL86	115				/	/
PRMSL118	150	33	49	47.5	32	/
PRMSL167	198				64	32
PRMSL199	230				64	32

### Front panel adjustment.

Panel left and right adjustment ±1.5mm.  
Panel up and down adjustment ±1.5mm.

### Slide mounting hole distance

Nominal length: 270/300/350/400  
Nominal length: 450/500/550

### The cabinet body rail mounting dimensions

The cabinet front  
37  
NL+3  
Drawer  
NL Nominal length

### Drawer disassembly.

The panel is disassembled.

### Drawer installation

① ② ③ ④ ⑤ ⑥

SB1900-B SB1900-C/D  
Arrowhead downward (for SB1900-B/C/D)

### Drawer removal