TIOMOS 120/-45A -45° corner cabinet hinge (overlay)



- For -45° angled cabinets
- 120° opening angle
- With convenient depth adjustment via worm screw
- 3-dimensional adjustment with corresponding mounting plate
- · Minimum reveals

Available in two versions:

- With integrated damper (3 adjustable damping levels)
- Without integrated damper

ORDER INFORMATION FOR DRILLING PATTERN 45/9.5, NICKEL

Door overlay		Damper		Without	Art. No.		
		With	Without		Click-on for screw fitting	Click-on for press fitting	
Overlay ¹		•	-	-	F028 138 557	F028 138 560	
Overlay		-		-	F045 138 495	F045 138 498	

 $^{^{\}rm 1}$ Cup material: steel, nickel-plated/Arm material: zamak, nickel-plated


PAGE REFERENCES

Tiomos mounting plates	86
Accessories	96
Technical information	100

Assembly technology	637
Assembly aids	654


PLANNING DIMENSIONS

All dimensions in millimetres




Mounting plate height 0

		Cup distance							
		3	4	5	6	7			
	12.0					0			
	11.5				0				
	10.5			0					
	9.5		0			2			
	8.5	0			2				
	8.0					3			
	7.5			2					
	7.0				3				
	6.5		2						
	6.0			3					
	5.5	2							
	5.0		3						
	4.5								
	4.0	3				6			
	3.5								
Door overlay	3.0				6				
	2.0			6					
	1.0		6						
2	0.0	6							
		Mounting plate height							



Cross mounting plates with mounting distance 37

	Mounting plate height							
	0 2 3 6							
Χ	60.5	62.5	63.5	66.5				
	Cross mounting plate position (X)							



Linear mounting plates

	Mounting plate height							
	0	2	3					
Х	43.5	45.5	46.5					
Linear mounting plate position (X)								

MINIMUM REVEAL


		Cup distance							
		3	4	5	6	7			
	24.0	6.4	5.4	4.4	3.4	2.4			
	22.0	3.0	2.0	1.5	1.5	1.5			
	21.0	1.4	1.3	1.3	1.3	1.3			
SS	20.0	1.1	1.1	1.1	1.1	1.1			
ķ	19.0	0.9	0.9	0.9	0.9	0.9			
Door thickness	18.0	0.7	0.7	0.7	0.7	0.7			
or t	17.0	1.0	1.0	1.0	1.0	1.5			
8	16.0	1.0	1.0	1.0	1.0	1.0			
		Minimum reveal (F)							

NOTES


Minimum reveal for doors with chamfered edges (R = 1 mm) with factory setting.

We recommend a trial fitting.

DRILLING PATTERNS 45/9.5



Impresso combination drilling pattern



CUP DIMENSIONS

